

# 2MP IR Vari-focal HDCVI Dome

Starlight HDCVI IR Dome Camera



**HDCVI**

- 1/2.8-in. 2MP Progressive-scan CMOS Sensor
- 1080p at 30 fps Maximum Resolution
- 2.7 mm to 12 mm Motorized Optical Zoom Lens
- Multi-format Output (HDCVI, CVBS, AHD, and TVI)
- HD and SD Output, Switchable
- Starlight Technology for Low-light Applications
- Maximum IR Length 30 m (98 ft), Smart IR
- IP67 Ingress Protection and IK10 Vandal Resistance
- Five-year Warranty\*



## System Overview

Experience the superior clarity of Dahua's 2MP HDCVI cameras for vast coverage and superior image details. The 2MP HDCVI series leverages existing coax infrastructures to deliver forensic-level images seamlessly and over long distances. The camera uses a progressive-scan CMOS sensor and next-generation ISP chip technology developed by Dahua to deliver stunning video with a wide field of view. This home-grown ISP features the latest image processing algorithms and is optimized for security camera operations. With total control of the ISP features and production, Dahua can offer the latest security systems at a cost-effective price.

## Functions

### Three Signals over One Coaxial Cable

HDCVI technology simultaneously transmits three signals (video, power, and data) over a single coaxial cable. Dual-way data transmission allows the HDCVI camera to communicate with an HCVR to send control signals or to trigger alarms. HDCVI along with PoC technology delivers power<sup>1</sup> to devices at the edge, simplifying installation.

### Long Distance Transmission

HDCVI technology guarantees real-time transmission over long distances without loss of video quality. HDCVI cameras provide the same resolution as most IP network camera systems using existing RG-59, RG-6, or CAT 6 UTP cabling.

### Starlight Technology

For challenging low-light applications, Dahua's Starlight low light Technology captures details in low light applications. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

## Simplicity

HDCVI technology seamlessly integrates traditional analog security systems with upgraded, high-quality HD video, making it the best choice to protect security investments. The plug and play approach enables full HD video security without the hassles of configuring a network.

## Smart IR

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of the camera's infrared LEDs to compensate for the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high-performance in extreme low-light environments up to 30 m (98 ft).

## Multi-format Support

The camera supports multiple video formats including, HDCVI, CVBS, AHD, and TVI. The camera can switch between these four formats via the OSD menu or the switch located on the video output cable, making the camera compatible with not only HDCVI DVRs but also most existing HD/SD DVRs

## Environmental

With a temperature range of -30 °C to +60 °C (-22 °F to +140 °F), the camera is designed for extreme temperature environments. The camera complies with an IK10 impact rating making it capable of withstanding the equivalent of 5 kg (11.02 lbs) of force dropped from a height of 40 cm (15.75 in.). Subjected and certified to rigorous dust and water immersion tests, the IP67 rating makes it suitable for demanding outdoor applications. Supporting a ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

1. Requires PoC Transceivers for each channel and an external 24 VDC or 36 VDC power supply for each transceiver.

Technical Specification

Camera	
Image Sensor	1/2.8-in. CMOS
Effective Pixels	1920(H) x 1080(V), 2MP
Scanning System	Progressive
Electronic Shutter Speed	1/30 to 1/100,000 s
Minimum Illumination	Color: 0.005 lux at F1.8 (30 IRE) 0 lux with IR on
S/N Ratio	More than 65 dB
IR Distance	Up to 30.0 m (98.43 ft)
IR On/Off Control	Auto, Manual
IR LEDs	Two (2)

Lens	
Lens Type	Motorized lens, Fixed iris
Mount Type	Board-in
Focal Length	2.7 mm to 12 mm
Max Aperture	F1.8
Horizontal Angle of View	101.7° to 32.3°
Focus Control	Motorized
Close Focus Distance	200.0 mm (7.87 in.)

DORI Distances <sup>2</sup>				
	Detect (8 ppf)	Observe (19 ppf)	Recognize (38 ppf)	Identify (76 ppf)
Wide	47 m (153 ft)	19 m (61 ft)	9 m (31 ft)	5 m (15 ft)
Tele	137 m (448 ft)	55 m (179 ft)	27 m (90 ft)	14 m (45 ft)

Installation Angle	
Range	Pan: 0° to 355° Tilt: 0° to 75° Rotation: 0° to 355°

2. The DORI distance is a measure of the general proximity for a specific classification to help pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specifications and lab test results according to EN 62676-4 , the standard that defines the criteria for the Detect, Observe, Recognize and Identify classifications.

3. Transmission distance results verified by real-scene testing in Dahua's test laboratory. Actual transmission distances may vary due to external influences, cable quality, and wiring structures.

Video		
Resolution	1080p (1920 x 1080)	
Frame Rate	1080p at 30 fps 720p at 30/60 fps	
Video Output	One (1) BNC HDCVI High-definition Channel or One (1) BNC CVBS, AHD or TVI Channel, switchable	
Video Transmission <sup>3</sup>	RG-59/U Coax	720p: 800 m (2624.67 ft) 1080p: 500 m (1640.42 ft)
	RG-6/U Coax	720p: 1200 m (3937.01 ft) 1080p: 800 m (2624.67 ft)
	CAT 6 UTP (balun required)	720p: 450 m (1476.38 ft) 1080p: 300 m (984.25 ft)
Day/Night	Auto (ICR), Manual	
On-screen Display Menu	Multi-language (Chinese, English, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, and Spanish)	
BLC Mode	BLC, HLC, DWDR	
WDR	Digital WDR	
Gain Control	AGC	
Noise Reduction	2D	
White Balance	Auto, Manual	
Smart IR	Auto, Manual	

Certifications	
Safety	UL60950-1+CAN/CSA C22.2 No.60950-1
Electromagnetic Compatibility (EMC)	FCC CFR 47 Part 15 Subpart B ANSI C63.4-2014 EN55032, EN55024, EN50130-4

Electrical	
Power Supply	12 VDC ±30%
Power Consumption	6.7 W Maximum (12 VDC, IR on)

Environmental	
Operating Conditions	−30° C to +60° C (−22° F to +140° F), Less than 90% RH Initiate startup above −30° C (−22° F)
Storage Conditions	−30° C to +60° C (−22° F to +140° F), Less than 90% RH
Ingress Protection	IP67
Vandal Resistance	IK10

Construction	
Casing	Aluminium
Dimensions	ø122.0 mm x 88.90 mm (ø4.80 in. x 3.50 in.)
Net Weight	0.44 kg (0.97 lb)
Gross Weight	0.59 kg (1.30 lb)

## Ordering Information

Type	Part Number	Description
2MP Camera	A21CM0Z	2MP Starlight HDCVI IR Dome Camera
Accessories, optional	PFA106	Mount Adapter (For use with PFB305W or PFB220C)
	PFA137	Junction Box (For use alone)
	PFA151	Corner Mount (For use with PFA106 and PFB305W)
	PFA152-E	Pole Mount (For use with PFB203W wall mount)
	PFB200C	In-ceiling Mount
	PFA200W	Sun/Rain Shield
	PFB203W	Wall Mount (For use alone or with PFA152-E pole mount)
	PFB220C	Ceiling Mount (For use with PFA106 mount adapter)
	PFB305W	Wall Mount (For use with PFA106 mount adapter)
	PFM800-E	Passive HDCVI Balun
	PFM800-4K	Passive 4K Video Balun
	DH-PFM321D-US	12 VDC, 1 A Power Adapter
	DH-PFM320D-US	12 VDC, 2 A Power Adapter

## Accessories


Optional:



PFA106  
Mount Adapter



PFA137  
Junction Box



PFA151  
Corner Mount



PFA152-E  
Pole Mount



PFA200W  
Sun/Rain Shield



PFB200C  
In-ceiling Mount



PFB203W  
Wall Mount



PFB220C  
Ceiling Mount



PFB305W  
Wall Mount



PFM800-E  
Passive HDCVI Balun



PFM800-4K  
Passive Video Balun



DH-PFM321D-US  
Power Adapter



DH-PFM320D-US  
Power Adapter

Junction Mount	In-ceiling Mount
PFA137	PFB200C
Wall Mount	Pole Mount
PFB203W	PFB203W + PFA152-E
Wall Mount with Rain Shade	Ceiling Mount (Extendable)
PFA137+PFA200W	PFA106+PFB220C
Pole Mount with Rain Shade	
PFA137+PFA200W+PFA152-E	

## Dimensions (mm/inch)

