

Waterproof Junction Box



- Aluminum alloy construction
- IP66 Rating



System Overview

Ideal for mounting cameras, it works in temperatures ranging from -40° C to $+60^{\circ}$ C (-40° F to $+140^{\circ}$ F) and in environments with relative humidity of less than 90%.

Technical Specification

Structure

Product Material		Aluminum Alloy		
Product Dimensions		Φ123.4 mm × 44.9 mm (Φ4.86 in. × 1.77 in.)		
Net Weight		0.39 kg (0.86 lb)		
Gross Weight		0.51 kg (1.12 lb)		
Maximum Load Bearing		3.0 kg (6.61 lb)		
Installation		Junction Mount		
Screw Thread Type		G3/4		
Packaging Dimensions $(L \times W \times H)$		187.0 mm × 164.0 mm × 72.0 mm (7.36 in. × 6.46 in. × 2.83 in.)		
Transport Package Dimensions $(L \times W \times H)$		578.0 mm × 383.0 mm × 349.0 mm (22.76 in.× 15.08 in. × 13.74 in.)		
Environment				
Protection		IP66		
Operating Temperature		-40 °C to 60 °C (-40 °F to 140 °F) < 90% (RH)		
Storage Temperature		-40 °C to 60 °C (-40 °F to 140 °F) 10% to 90% (RH)		
Ordering Information				
Type	Part Number	Description		


Туре	Part Number	
Camera	DH-PFA5300R	
Mount	DH-FFAJ300N	

Description Waterproof Junction Box

Packaging Information

Description	Quantity
Waterproof Junction Box	1
M4 × 10 Screws	4
ST4 × 25 Screws	3
Plastic Expansion Bolt	3
S3.0 Wrench	1
Water Joint	1
Mounting Sticker	1

Dimensions



us.dahuasecurity.com