

28-inch Ultra-HD LED Monitor

4K Ultra-high-definition Display



- High-resolution Display Up to 3840 x 2160
- IPS Panel Technology
- 178°H/178°V Extra-wide Viewing Angle for Overall Viewing Performance
- Screen Surface With a Hardness of at Least 3h
- Supports Multiple Signal Interfaces
- Compatible with VESA Mounting Pattern 75 mm X 75 mm

Technical Specification

Display	
Screen Size	28 in.
Aspect Ratio	16:9
Resolution	3840 x 2160 (UHD)
Backlight	LED
Brightness/Luminance	300 cd/m ²
Contrast	1000:1
Display Color	1.07B
View Angle (H/V)	178°/178°
Tilt	-5° to 15°
Response Time (typ.)	5 ms
Refresh Rate	60 Hz
Freesync	Supported

Interface	
Input	One (1) DP 1.2, Two (2) HDMI 2.0
Output	One (1) USB (for charging)
Speaker	Two (2) 2W

Electrical	
Power Supply	AC 100-240V
Power Consumption	40 W

Environmental	
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Operating Humidity	10% to 85% RH

Construction	
Dimensions w/o Standard (W x H x D)	637.88 mm x 368.53 mm x 57.36 mm (25.11 in. x 14.51 in. x 2.26 in.)
VESA	75 mm x 75 mm (3.0 in. x 3.0 in.)
Net Weight	7 kg (15.43 lb)
Gross Weight	8.8 kg (19.40 lb)

Certifications	
CE	EN 62368-1:2014+A11:2017 IEC 62368-1:2014 EN 55032:2015+A11:2020 EN 55035:2017+A11:2020 EN 50130-4:2011+A1:2014 EN IEC 61000-3 2:2019 EN 61000-3 3:2013+A1:2019
FCC	FCC CFR Title 47 Part 15 Subpart B

Ordering Information

Type	Part Number	Description
Display	DHI-LM28-F400	28-inch UHD Monitor

Package Contents

- 1 x HDMI Cable
- 1 x Power Cable
- 1 x Pedestal

Dimensions

mm

