

# 4MP Enhanced Starlight Network PTZ Camera (25x)

## WizSense Analytics and ArcticPro





WizSense Series devices combine Dahua's powerful Analytics+ with an intuitive and easy to use interface. WizSense devices offer Smart Motion Detection and Perimeter Protection functions that focus on human and vehicular images and ignore irrelevant images to capture important video while reducing false alarms. WizSense Series devices provide powerful general security for small to medium size businesses at a sensible price.

### System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, this camera provides an all-in-one solution for capturing long distance video security for outdoor applications. Together with infrared illumination and Enhanced Starlight Technology, the camera is the perfect solution for dark, lowlight applications. The series combines a day/night mechanical IR cut filter for the highest image quality in variable lighting conditions during the day.

### Functions

#### Enhanced Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low light Technology offers best-in-class light sensitivity, capturing details in low light applications down to 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

#### Perimeter Protection

Dahua Analytics+ includes Tripwire and Intrusion functions that offer custom tripwires based on object type for automation in limited access areas. Perimeter Protection requires fewer pixels to detect an object to deliver improved accuracy and decreased false alarms due to lights, weather, trees, or animals.

#### Face Detection

Face Detection technology captures a human face in a digital image and then selects the best image and outputs a snapshot of the face.

#### Smart Motion Detection+

Smart Motion Detection+, a component of Dahua's Analytics+ technology, improves alarm accuracy and decreases the number of false alarms. The advanced SMD+ algorithm analyzes a scene for human or vehicle motion, while filtering out other motion due to trees, leaves, animals, weather, and triggers an alarm when detected.

- 1/2.8-in. STARVIS™ CMOS Sensor
- Powerful 25x Optical Zoom Lens
- Enhanced Starlight Technology for Low-light Applications
- AI Coding and Smart H.265+ and Smart H.264+ Smart Dual Codec
- Enhanced Starlight Technology for Low-light Applications
- 4MP (2560 x 1440) at 30 fps
- Maximum IR LED Distance of 100 m (328.08 ft)
- Analytics+ Functions: Perimeter Protection, Face Detection, Smart Motion Detection+
- ArcticPro Series Camera - Operational down to  $-40^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$ )
- IP66 Ingress Protection, TVS 6000 V Surge Protection
- Five-year Warranty\*



#### Smart H.265+ and Smart H.264+

Delivering high quality video without straining the network, Smart H.264+ is the optimized implementation of H.264. The Smart H.264+ encoding platform includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing a savings of up to 70% of bandwidth and storage when compared with standard H.264.

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

#### ArcticPro (No Heater)

The Dahua ArcticPro Series of extreme-environment cameras combine temperature-tolerant components with a waterproof enclosure to ensure flawless operation in temperatures as low as  $-40^{\circ}\text{C}$  ( $-40^{\circ}\text{F}$ ) without the need for an internal heater. The lack of a heater reduces the camera's power consumption and saves operating costs. For applications that demand high-resolution video with advanced features in extremely cold environments, the Dahua ArcticPro Series offers a camera to satisfy the most demanding requirements.

#### Environmental

Subjected to rigorous dust and water immersion tests and certified to the IP66 Ingress Protection rating makes it suitable for demanding outdoor applications.

Supporting dual voltage input (12 VDC or 24 VAC) and a  $\pm 25\%$  input voltage tolerance, this camera suits even the most unstable power supply conditions. Its TVS 6000 V lightning rating protects the camera and its structure from the effects of lightning on the camera and its structure.

**Technical Specification**

<b>Camera</b>		
Image Sensor	1/2.8-in. CMOS	
Effective Pixels	2560 (H) × 1440 (V)	
RAM/ROM	1 GB/4 GB	
Scanning System	Progressive	
Electronic Shutter Speed	1/1 s to 1/30,000 s	
Minimum Illumination	Color	0.005 lux at F1.6
	B/W	0.0005 lux at F1.6
	IR Light On	0 lux at F1.6
IR Distance	100 m (328.08 ft)	
IR On/Off Control	Zoom Priority, Manual, Smart IR, Off	
Illuminator Number	Four (4) IR LEDs	

<b>Lens</b>				
Focal Length	5 mm to 125 mm			
Maximum Aperture	F1.6 to F3.6			
Angle of View	Horizontal	53.1° to 3.4°		
	Vertical	30.4° to 1.9°		
	Diagonal	59.3° to 3.9°		
Optical Zoom	25x			
Focus Control	Automatic, Semi-automatic, Manual			
Iris Control	Auto			
Close Focus Distance	1 m to 9 m (3.28 ft to 29.53 ft)			
DORI' Distance	Detect	Observe	Recognize	Identify
	2161.4 m (7091.21 ft)	864.6 m (2836.61 ft)	432.3 m (1418.30 ft)	216.1 m (708.99 ft)

<b>PTZ</b>		
Pan/Tilt Range	Pan	0° to 360° endless
	Tilt	-15° to +90°, auto flip 180°
Manual Control Speed	Pan	0.1° to 200°/s
	Tilt	0.1° to 120°/s
Preset Speed	Pan	240°/s
	Tilt	200°/s
Presets	300	
PTZ Mode	5 Patterns, 8 Tours (Up to 32 Presets per Tour), 5 Scans	
Power Up Action	Auto restore to previous PTZ and lens status after power failure	
Idle Motion	Activate Preset/Scan/Tour/Pattern if there is no command in the specified period	

<b>Video</b>		
Video Compression	AI Coding, H.264H, H.264B, Smart H.265+, H.264, H.265, MJPEG(Sub Stream), Smart H.264+	
Streaming Capability	Three (3) Streams	
Resolution	4MP (2560 × 1440), 3MP (2048 × 1536), 2304 × 1296, 1080p (1920 × 1080), 720p (1280 × 720), D1 (704 × 576/704 × 480), CIF (352 × 288/352 × 240)	
Frame Rate	Main Stream	4MP/3MP/1080p/1.3MP/720p at 1 to 30 fps
	Sub Stream 1	D1/CIF at 1 to 30 fps
	Sub Stream 2	1080p/1.3M/720p at 1 to 30 fps
Bit Rate Control	CBR/VBR	
Bit Rate	H.264	96 to 14,848 Kbps
	H.265	38 to 8,960 Kbps
Day/Night	Auto (ICR), Color, B/W	
Backlight Compensation	BLC, WDR, HLC	
White Balance	Auto, Indoor, Outdoor, Tracking, Manual, Sodium Lamp, Natural Light, Street Lamp	
Gain Control	Auto, Manual	
Noise Reduction	2D, 3D	
Advanced Features	Region of Interest (RoI), Electronic Image Stabilization (EIS), Defog	

Digital Zoom	16x
Image Rotation	180°
Privacy Masking	Up to 24 areas (8 areas allowed per view)
S/N Ratio	≥ 55 dB

<b>Audio</b>	
Compression	PCM, G.711a, G.711Mu, G.726, MPEG2-Layer2, G.722.1, G.729, G.723, AAC

<b>Network</b>	
Ethernet	One (1) RJ-45 Port (10/100 Base-T)
Protocol	FTP, RTMP, IPv6, Bonjour, IPv4, DNS, RTCP, PPPoE, NTP, RTP, 802.1x, HTTPS, SNMP, TCP/IP, DDNS, UPnP, NFS, ICMP, UDP, IGMP, HTTP, SSL, DHCP, SMTP, Qos, RTSP, ARP
Interoperability	RTMP, CGI, SDK, ONVIF (Profile S, G, T), P2P
Streaming Method	Unicast/Multicast
Maximum User Access	20 Users (Total Bandwidth 64 Mbps)
Edge Storage	Micro SD Slot (Max. 512 GB), FTP/SFTP, NAS
Browser	Safari (iOS 10 or Later), Microsoft Edge, Google Chrome 41 or Later, Firefox 50 or Later
Management Software	DSS, DMSS
Mobile Client	iOS, Android

<b>Certifications</b>	
CE	CE-EMC: EN 55032; EN 61000-3-3; EN 61000-3-2; EN 50130-4; EN 55035; CE-LVD: EN 62368-1
FCC	47 CFR FCC Part15, Subpart B, NSI C63.4
UL	UL62368-1

<b>Interface</b>		
Audio	Input	One (1) channel (LINE IN, bare wire)
	Output	One (1) channel (LINE OUT, bare wire)
Alarm	Input	Two (2) Channel
	Output	One (1) Channel
Alarm Linkage	Capture, Recording, Send Email, Preset, Tour, Pattern, Alarm Digital Input	
Alarm Event	Motion/Tampering Detection, Audio Detection, Network Disconnection Detection, IP Conflict Detection, Memory Card State Detection, Memory Space Detection	

<b>Electrical</b>		
Power Supply	12 VDC/3A±10%, PoE (802.3at)	
Power Consumption	Basic	9 W
	Maximum	20 W (Illuminator + Alarm + PTZ)

<b>Environmental</b>	
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Operating Humidity	≤ 95%
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Storage Humidity	≤ 95%
Ingress Protection	IP66
Surge Protection	TVS 6000 V

<b>Construction</b>	
Product Dimensions	270.4 mm × Φ160 mm (10.65" × Φ6.30")
Net Weight	2.4 kg (5.29 lb)
Gross Weight	3.9 kg (8.60 lb)

<b>Analytics+ Functions</b>	
Face Detection	<ul style="list-style-type: none"> <li>Detects and captures a snapshot of a human face in a defined area within a scene.</li> </ul>
Smart Motion Detection	<ul style="list-style-type: none"> <li>Differentiates between and classifies human and vehicle objects.</li> <li>Filters false alarms due to leaves, lights, animals, and other inconsequential objects.</li> <li>Extracts human or vehicle objects from recorded video for quick target search and retrieval.</li> </ul>

Perimeter Protection	<ul style="list-style-type: none"> <li>Detects human violations using the following methods:                             <ul style="list-style-type: none"> <li><b>Tripwire:</b> a target crosses a defined line.</li> <li><b>Intrusion:</b> a target enters or exits a defined perimeter.</li> </ul> </li> <li>Monitors a combination of detection methods.</li> </ul>
----------------------	---

Intelligent Video System (IVS) Functions

IVS triggers an alarm and takes a defined action for the following events:	
Standard Features	Tampering with the camera. Error writing to an onboard Micro SD card. Error sending or receiving data over the network. Unauthorized access to the camera.
Premium Features	
Tripwire	A target crosses a user-defined line.
Intrusion	A target enters or exits a defined perimeter.
Abandoned/Missing Object	A target leaves an object in designated area, or a target removes an object from the same designated area.
Advanced Features	
Loitering Detection	Target is in motion inside a defined area longer than a specified amount of time.
Fast Moving	Target exceeds a set speed when exiting a defined area.
Parking Detection	Vehicle remains in a defined area without motion for a set period of time.
Crowd Gathering	Specified number of people remain inside a defined area for a set time.
Human/Vehicle Classification	Detects human or vehicle violations using Tripwire or Intrusion detection methods.

Ordering Information

Type	Part Number	Description
Network Camera	49425GBNR	4MP 25x Starlight IR Network PTZ Camera
Accessories (Included)	PFB305W	Wall Mount Bracket
Accessories (Optional)	PFA120	Junction Box
	PFA111	Mount Adapter
	PFB300C	Ceiling Mount Bracket
	PFA150	Pole Mount Bracket
	PFA151	Corner Mount Bracket
	PFB303S	Parapet Mount Bracket
	DH-PFB301S-E	Plane Mount Bracket
S042-1A120300HU	12 VDC, 3 A Power Adapter	

For all possible accessory combinations for this camera, please scan or click the QR code below to go to our accessory selector.



Accessories

Included:



PFB305W  
Wall Mount Bracket

Optional:



PFA120  
Junction Box



PFA111  
Mount Adapter



PFB300C  
Ceiling Mount Bracket



PFA150  
Pole Mount Bracket



PFA151  
Corner Mount Bracket



PFB303S  
Parapet Mount Bracket



DH-PFB301S-E  
Plane Mount Bracket



S042-1A120300HU  
12 VDC, 3 A Power Adapter

Installation

Ceiling Mount	Ceiling Mount	Wall Mount
No Accessory	PFB300C	PFB303W
Pole Mount (Vertical)	Corner Mount	Parapet Mount
PFB150 + PFB303W	PFA151 + PFB303W	PFB303S

Dimensions

mm [in.]

