

4MP Enhanced Starlight Network PTZ Camera (25x)

WizSense Analytics and ArcticPro



WizSense



WizSense Series devices combine Dahua's powerful Analytics+ with an intuitive and easy to use interface. WizSense devices offer Smart Motion Detection and Perimeter Protection functions that focus on human and vehicular images and ignore irrelevant images to capture important video while reducing false alarms. WizSense Series devices provide powerful general security for small to medium size businesses at a sensible price.

System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, this camera provides an all-in-one solution for capturing long distance video security for outdoor applications. Together with infrared illumination and Enhanced Starlight Technology, the camera is the perfect solution for dark, lowlight applications. The series combines a day/night mechanical IR cut filter for the highest image quality in variable lighting conditions during the day.

Functions

Enhanced Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low light Technology offers best-in-class light sensitivity, capturing details in low light applications down to 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Perimeter Protection

Dahua Analytics+ includes Tripwire and Intrusion functions that offer custom tripwires based on object type for automation in limited access areas. Perimeter Protection requires fewer pixels to detect an object to deliver improved accuracy and decreased false alarms due to lights, weather, trees, or animals.

Face Detection

Face Detection technology captures a human face in a digital image and then selects the best image and outputs a snapshot of the face.

Smart Motion Detection+

Smart Motion Detection+, a component of Dahua's Analytics+ technology, improves alarm accuracy and decreases the number of false alarms. The advanced SMD+ algorithm analyzes a scene for human or vehicle motion, while filtering out other motion due to trees, leaves, animals, weather, and triggers an alarm when detected.

- 1/2.8-in. STARVIS™ CMOS Sensor
- Powerful 25x Optical Zoom Lens
- Enhanced Starlight Technology for Low-light Applications
- AI Coding and Smart H.265+ and Smart H.264+ Smart Dual Codec
- Enhanced Starlight Technology for Low-light Applications
- 4MP (2560 x 1440) at 30 fps
- Maximum IR LED Distance of 100 m (328.08 ft)
- Analytics+ Functions: Perimeter Protection, Face Detection, Smart Motion Detection+
- ArcticPro Series Camera - Operational down to -40° C (-40° F)
- IP66 Ingress Protection, TVS 6000 V Surge Protection
- Five-year Warranty*



Smart H.265+ and Smart H.264+

Delivering high quality video without straining the network, Smart H.264+ is the optimized implementation of H.264. The Smart H.264+ encoding platform includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing a savings of up to 70% of bandwidth and storage when compared with standard H.264.

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

ArcticPro (No Heater)

The Dahua ArcticPro Series of extreme-environment cameras combine temperature-tolerant components with a waterproof enclosure to ensure flawless operation in temperatures as low as -40° C (-40° F) without the need for an internal heater. The lack of a heater reduces the camera's power consumption and saves operating costs. For applications that demand high-resolution video with advanced features in extremely cold environments, the Dahua ArcticPro Series offers a camera to satisfy the most demanding requirements.

Environmental

Subjected to rigorous dust and water immersion tests and certified to the IP66 Ingress Protection rating makes it suitable for demanding outdoor applications.

Supporting dual voltage input (12 VDC or 24 VAC) and a ±25% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its TVS 6000 V lightning rating protects the camera and its structure from the effects of lightning on the camera and its structure.

Technical Specification				
Camera				
Image Sensor		1/2.8-in. CMOS		
Effective Pixels		2560 (H) × 1440 (V)		
RAM/ROM		1 GB/4 GB		
Scanning System		Progressive		
Electronic Shutter Speed		1/1 s to 1/30,000 s		
Minimum Illumination	Color	0.005 lux at F1.6		
	B/W	0.0005 lux at F1.6		
	IR Light On	0 lux at F1.6		
IR Distance		100 m (328.08 ft)		
IR On/Off Control		Zoom Priority, Manual, Smart IR, Off		
Illuminator Number		Four (4) IR LEDs		
Lens				
Focal Length		5 mm to 125 mm		
Maximum Aperature		F1.6 to F3.6		
Angle of View	Horizontal	53.1° to 3.4°		
	Vertical	30.4° to 1.9°		
	Diagonal	59.3° to 3.9°		
Optical Zoom		25x		
Focus Control		Automatic, Semi-automatic, Manual		
Iris Control		Auto		
Close Focus Distance		1 m to 9 m (3.28 ft to 29.53 ft)		
DORI' Distance	Detect	Observe	Recognize	Identify
	2161.4 m (7091.21 ft)	864.6 m (2836.61 ft)	432.3 m (1418.30 ft)	216.1 m (708.99 ft)
PTZ				
Pan/Tilt Range	Pan	0° to 360° endless		
	Tilt	−15° to +90°, auto flip 180°		
Manual Control Speed	Pan	0.1° to 200°/s		
	Tilt	0.1° to 120°/s		
Preset Speed	Pan	240°/s		
	Tilt	200°/s		
Presets		300		
PTZ Mode		5 Patterns, 8 Tours (Up to 32 Presets per Tour), 5 Scans		
Power Up Action		Auto restore to previous PTZ and lens status after power failure		
Idle Motion		Activate Preset/Scan/Tour/Pattern if there is no command in the specified period		
Video				
Video Compression		AI Coding, H.264H, H.264B, Smart H.265+, H.264, H.265, MJPEG(Sub Stream), Smart H.264+		
Streaming Capability		Three (3) Streams		
Resolution		4MP (2560 × 1440), 3MP (2048 × 1536), 2304 × 1296, 1080p (1920 × 1080), 720p (1280 × 720), D1 (704 × 576/704 × 480), CIF (352 × 288/352 × 240)		
Frame Rate	Main Stream	4MP/3MP/1080p/1.3MP/720p at 1 to 30 fps		
	Sub Stream 1	D1/CIF at 1 to 30 fps		
	Sub Stream 2	1080p/1.3M/720p at 1 to 30 fps		
Bit Rate Control		CBR/VBR		
Bit Rate	H.264	96 to 14,848 Kbps		
	H.265	38 to 8,960 Kbps		
Day/Night		Auto (ICR), Color, B/W		
Backlight Compensation		BLC, WDR, HLC		
White Balance		Auto, Indoor, Outdoor, Tracking, Manual, Sodium Lamp, Natural Light, Street Lamp		
Gain Control		Auto, Manual		
Noise Reduction		2D, 3D		
Advanced Features		Region of Interest (RoI), Electronic Image Stabilization (EIS), Defog		

Digital Zoom		16x
Image Rotation		180°
Privacy Masking		Up to 24 areas (8 areas allowed per view)
S/N Ratio		≥ 55 dB
Audio		
Compression		PCM, G.711a, G.711Mu, G.726, MPEG2-Layer2, G.722.1, G.729, G.723, AAC
Network		
Ethernet		One (1) RJ-45 Port (10/100 Base-T)
Protocol		FTP, RTMP, IPv6, Bonjour, IPv4, DNS, RTCP, PPPoE, NTP, RTP, 802.1x, HTTPS, SNMP, TCP/IP, DDNS, UPnP, NFS, ICMP, UDP, IGMP, HTTP, SSL, DHCP, SMTP, Qos, RTSP, ARP
Interoperability		RTMP, CGI, SDK, ONVIF (Profile S, G, T), P2P
Streaming Method		Unicast/Multicast
Maximum User Access		20 Users (Total Bandwidth 64 Mbps)
Edge Storage		Micro SD Slot (Max. 512 GB), FTP/SFTP, NAS
Browser		Safari (iOS 10 or Later), Microsoft Edge, Google Chrome 41 or Later, Firefox 50 or Later
Management Software		DSS, DMSS
Mobile Client		iOS, Android
Certifications		
CE		CE-EMC: EN 55032; EN 61000-3-3; EN 61000-3-2; EN 50130-4; EN 55035; CE-LVD: EN 62368-1
FCC		47 CFR FCC Part15, Subpart B, NSI C63.4
UL		UL62368-1
Interface		
Audio	Input	One (1) channel (LINE IN, bare wire)
	Output	One (1) channel (LINE OUT, bare wire)
Alarm	Input	Two (2) Channel
	Output	One (1) Channel
Alarm Linkage		Capture, Recording, Send Email, Preset, Tour, Pattern, Alarm Digital Input
Alarm Event		Motion/Tampering Detection, Audio Detection, Network Disconnection Detection, IP Conflict Detection, Memory Card State Detection, Memory Space Detection
Electrical		
Power Supply		12 VDC/3A±10%, PoE (802.3at)
Power Consumption	Basic	9 W
	Maximum	20 W (Illuminator + Alarm + PTZ)
Environmental		
Operating Temperature		−40 °C to +70 °C (−40 °F to +158 °F)
Operating Humidity		≤ 95%
Storage Temperature		−40 °C to +70 °C (−40 °F to +158 °F)
Storage Humidity		≤ 95%
Ingress Protection		IP66
Surge Protection		TVS 6000 V
Construction		
Product Dimensions		270.4 mm × Φ160 mm (10.65" × Φ6.30")
Net Weight		2.4 kg (5.29 lb)
Gross Weight		3.9 kg (8.60 lb)
Analytics+ Functions		
Face Detection		<ul style="list-style-type: none">Detects and captures a snapshot of a human face in a defined area within a scene.
Smart Motion Detection		<ul style="list-style-type: none">Differentiates between and classifies human and vehicle objects.Filters false alarms due to leaves, lights, animals, and other inconsequential objects.Extracts human or vehicle objects from recorded video for quick target search and retrieval.

Perimeter Protection	<ul style="list-style-type: none">• Detects human violations using the following methods: Tripwire: a target crosses a defined line. Intrusion: a target enters or exits a defined perimeter.• Monitors a combination of detection methods.
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Intelligent Video System (IVS) Functions

IVS triggers an alarm and takes a defined action for the following events:	
Standard Features	Tampering with the camera. Error writing to an onboard Micro SD card. Error sending or receiving data over the network. Unauthorized access to the camera.
Premium Features	
Tripwire	A target crosses a user-defined line.
Intrusion	A target enters or exits a defined perimeter.
Abandoned/Missing Object	A target leaves an object in designated area, or a target removes an object from the same designated area.
Advanced Features	
Loitering Detection	Target is in motion inside a defined area longer than a specified amount of time.
Fast Moving	Target exceeds a set speed when exiting a defined area.
Parking Detection	Vehicle remains in a defined area without motion for a set period of time.
Crowd Gathering	Specified number of people remain inside a defined area for a set time.
Human/Vehicle Classification	Detects human or vehicle violations using Tripwire or Intrusion detection methods.

Ordering Information		
Type	Part Number	Description
Network Camera	49425GBNR	4MP 25x Starlight IR Network PTZ Camera
Accessories (Included)	PFB305W	Wall Mount Bracket
Accessories (Optional)	PFA120	Junction Box
	PFA111	Mount Adapter
	PFB300C	Ceiling Mount Bracket
	PFA150	Pole Mount Bracket
	PFA151	Corner Mount Bracket
	PFB303S	Parapet Mount Bracket
	DH-PFB301S-E	Plane Mount Bracket
	S042-1A120300HU	12 VDC, 3 A Power Adapter

For all possible accessory combinations for this camera, please scan or click the QR code below to go to our accessory selector.



Accessories

Included:



PFB305W
Wall Mount Bracket

Optional:



PFA120
Junction Box



PFA111
Mount Adapter



PFB300C
Ceiling Mount Bracket



PFA150
Pole Mount Bracket



PFA151
Corner Mount Bracket



PFB303S
Parapet Mount Bracket



DH-PFB301S-E
Plane Mount Bracket



S042-1A120300HU
12 VDC, 3 A Power Adapter

Installation

Wall Mount	Ceiling Mount	Ceiling Mount
PFB305W+PFA120	PFA111+PFB300C	PFA111+PFB301C
Pole Mount(Vertical)	Corner Mount	Pole Mount(Horizontal)
PFB305W+PFA150	PFB305W+PFA151	PFA111+PFB300C+PFA150
Plane Mount	Parapet Mount	
PFB301S-E	PFA111+PFB303S	

Dimensions

mm [in.]

