

In-ceiling Mount Bracket



- SECC and PC Construction
- Simple and Convenient Installation
- Compatible with 4A425DBNR

System Overview

The DH-PFB5310C supports in-ceiling mounting The bracket is designed to suit complex scenes, making it convenient to use in environments with high temperatures, humidity, and corrosivity. It is ideal for mounting cameras in temperatures ranging from $-40\,^{\circ}\text{C}$ to $60\,^{\circ}\text{C}$ ($-40\,^{\circ}\text{F}$ to $140\,^{\circ}\text{F}$) and in environments with relative humidity of less than 90%.

Technical Specification

Construction

Material	SECC, PC
Dimensions	238.0 mm × 78.0 mm (9.37 in. × 3.07 in.)
Color	White
Net Weight	0.35 kg (0.77 lb)
Gross Weight	0.62 kg (1.37 lb)
Load Bearing Weight	3.0 kg (6.61 lb)
Package Dimensions (L \times W \times H)	286.0 mm × 286.0 mm × 120.0 mm (11.26 in. × 11.26 in. × 4.72 in.)

Environment

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	< 90% (RH)
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	10% to 90% (RH)
Anti-Corrosion Level	Basic Protection

Ordering Information		
Туре	Part Number	Description
Camera	DH-PER5310C	In-ceiling Mount Bracket

For all possible accessory combinations for this camera, please scan or click the QR code below to go to our accessory selector.



Packaging Information

- 1 x In-Ceiling Mount Bracket
- 1 x M4 x 4 Screw
- 1 x Anti-Drop Rope
- 1 x Installation Guide

Dimensions

