

Pole Mount Bracket



- SECC and SUS304 Construction
- Simple and Convenient Installation
- Enhanced Buckle for Better Support

System Overview

The DH-PFA5500 supports installation methods such as a wall mount, pole mount, corner mount and in-ceiling mount. The bracket is designed to suit complex scenes, making it convenient to use in environments with high temperatures, humidity, and corrosivity. It is ideal for mounting cameras in temperatures ranging from $-40\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $+140\text{ }^{\circ}\text{F}$) and in environments with relative humidity of less than 90%.

Technical Specification

Material	SECC and SUS304 Stainless Steel
Packaging Dimensions (L x W x H)	237.0 mm x 164.0 mm x 191.0 mm (9.33 in. x 6.46 in. x 7.52 in.)
Product Dimensions (L x W x H)	130.4 mm x 170.0 mm x 45.0 mm (5.13 in. x 6.69 in. x 1.77 in.)
Net Weight	1.31 kg (2.89 lb)
Gross Weight	1.57 kg (3.46 lb)
Load Bearing	15.0 kg (33.07 lb)
Installation	Pole Mount
Pole Diameter	80 mm to 150 mm (3.15 in. to 5.91 in.)

Environment

Operating Temperature	$-40\text{ }^{\circ}\text{C}$ to $60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $140\text{ }^{\circ}\text{F}$)
Operating Humidity	< 90% (RH)
Storage Temperature	$-40\text{ }^{\circ}\text{C}$ to $80\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $176\text{ }^{\circ}\text{F}$)
Storage Humidity	10% to 90% (RH)

Ordering Information

Type	Part Number	Description
Accessory	DH-PFA5500	Pole Mount Bracket

Packaging Information

- One (1) Pole Mount Bracket
- Four (4) M8 x 25 Screws
- Three (3) 80 mm to 150 mm Metal Hoops
- One (1) S6.0 Wrench

Dimensions

